



## PLASTAZOTE® FOAM

FLAME RETARDANT METALLOCENE CATALIZED POLYETHYLENE FOAM

### MP GRADES GREY

ALL DENSITIES

## SAFETY INFORMATION SHEET

The "REACH" Regulation EC No 1907/2006 of the European Parliament and of the Council dated 18 December 2006 requires suppliers of substances and preparations to provide safety datasheets for substances of concern as defined in Article 31 of the regulation. Our foam products are classed as non hazardous under EU regulations (CLP, REACH) and the Global Harmonised System (GHS). Under REACH our foam products are not considered as substances or preparations but as articles as defined in Article 33 of the regulation. Safety datasheets are not required for articles however to continue providing our customers with guidance relating to the safe handling and information on the composition of our foam products this safety information sheet has been prepared with reference to EC Regulation 1907/2006 Annex II.

### 1. Identification of the Substance or Preparation and of the Company

#### 1.1 Product Name

Plastazote® MP FR - all densities - grey

#### 1.2 Use of the Product

Foam sheet to be used as produced or for conversion into articles. Applications include but are not limited to construction, industrial, medical, packaging or transport applications.

#### 1.3 Company

Zotefoams plc  
675 Mitcham Road  
Croydon  
CR9 3AL  
United Kingdom  
email: msds@zotefoams.com

#### 1.4 Emergency Contact

Director of Technology & Development  
Telephone: +44 (0) 208 664 1600

### 2. Hazard Identification

In the event of fire, decomposition products may include acrolein, other aldehydes, halogens, hydrogen halides, antimony compounds, carbon monoxide and carbon dioxide.

May generate static electricity.

### 3. Composition / Information on Ingredients

Chemical Name	CAS number	EINECS number	Risk phrases	Content in weight %
Polyethylene	9002-88-4	n/a	-	75 - 85
Ethylene Methylacrylate Copolymer	25103-74-6	n/a	-	10 - 12
Carbon Black	1333-86-4	215-609-9	-	0 - 1
Antimony Trioxide	1309-64-4	215-175-0	R40	2 - 3
Halogenated Additive				5 - 7

### 4. First Aid Measures

Inhalation: No hazard in normal use  
Skin Contact: No hazard in normal use  
Eye Contact: Wash with Water  
Ingestion: Wash mouth and seek medical advice



# ZOTEFOAMS

## PLASTAZOTE® FOAM

FLAME RETARDANT METALLOCENE CATALIZED POLYETHYLENE FOAM

### MP GRADES GREY

ALL DENSITIES

## SAFETY INFORMATION SHEET

---

### 5. Fire-Fighting Measures

Water spray recommended, other extinguishing agents may be used

Decomposition products may include acrolein, other aldehydes, halogens, hydrogen halides, antimony compounds, carbon monoxide and carbon dioxide.

### 6. Accidental Release Measures

Not relevant

### 7. Handling and Storage

#### 7.1 Handling

Provision should be made for sufficient ventilation and local exhaust where dust/fumes may be produced. Avoid dust generation. Where dust is produced, measure must be taken to avoid static electricity discharge. Equipment used should be electrically earthed and fitted with static elimination devices.

#### 7.2 Storage

Store in a dry well ventilated area away from direct sunlight, heat and ignition sources. The appropriate company regulations for fire prevention are to be followed.

Keep away from strong oxidising agents.

### 8. Exposure Controls / Personal Protection

No special precautions are necessary.

### 9. Physical and Chemical Properties

#### 9.1 General Information

Appearance: Foam  
Odour: None

#### 9.2 Important health, safety and environmental information

Flash point: >300°C  
Autoflammability: >300°C  
Decomposition  
Explosive properties: None  
Vapour pressure: Not Applicable  
Relative density: Polymer 0.915 g/cm<sup>3</sup>  
Foam 0.015 g/cm<sup>3</sup>  
Solubility in water: Insoluble

#### 9.3 Other Information

Melting Point: ~104°C by DSC

### 10. Stability and Reactivity

#### 10.1 Conditions to avoid

Contact with sources of ignition. Decomposes above 300°C

#### 10.2 Materials to avoid

