

AZOTE®

INSULATION

High performance foam



ZOTEFOAMS

AZOTE®

Insulation

AZOTE® foams offer a unique combination of advantages for Construction, HVAC and Road Transport Industry design teams.


AZOTE® lightweight, low odour, crosslinked polyolefin block foams possess best in class flammability credentials. These foams are also lightweight and mould resistant and are renowned for their thermal and acoustic insulation performance.

The range also has conductive and static dissipative grades compatible with sensitive electronic components, and a huge colour range.

These foams provide the vital high performance insulation component in a wide range of applications including heating & hot water systems, flooring underlay, window seals and roof & wall insulation.

The Zotefoams process produces lightweight, low odour, crosslinked, closed cell foams with amazingly consistent cell size.

The inbuilt characteristics of AZOTE® foam facilitate the production of high quality finished products from a wide variety of processes, including thermoforming, water jet cutting, thermal bonding and routing.



Insulation applications

Construction

- ◆ Heating Systems
- ◆ Hot Water Systems
- ◆ Wall Insulation
- ◆ HVAC
- ◆ Window Seals
- ◆ Flooring Underlay
- ◆ Expansion Joint Fillers
- ◆ Frost Blankets
- ◆ Roof Insulation
- ◆ Eaves Fillers



Standards

	Test Method	Plastazote® MP15EB40 Result	Plastazote® LD24FM Result
Flammability	EUROCLASS EN 13501:2007	B, s1, d0	B, s1, d0
Water Absorption	ISO 2896:2001 Ed3.	<2%	<2%
Thermal Conductivity	ISO 8301:1991	0.037 W/mK	0.034 W/mK

AZOTE®

The AZOTE® Insulation
Design Premium



LIGHTWEIGHT



COLD RESISTANT



**IMPACT
RESISTANT**



**CONSISTENT CELL
SIZE & STRUCTURE**



DURABLE



HEAT RESISTANT



LOW ODOUR & VOC'S



**RESISTANT TO
SOME CHEMICALS**



**THERMAL
INSULATION**



**BARRIER TO
MOISTURE**



**MOULD
RESISTANT**



**FLAME
RETARDANT**



ZOTEFOAMS

For more information

ZOTEFOAMS plc

675 Mitcham Road
Croydon CR9 3AL United Kingdom
Tel: +44 (0) 20 8664 1600
Fax: +44 (0) 20 8664 1616
Email: info@zotefoams.com

ZOTEFOAMS, inc

55 Precision Drive
Walton Kentucky 41094 USA
Tel: +1 859 371 4046 FREE: (800) 362-8358 (US Only)
Fax: +1 859 371 4734
Email: custserv@zotefoams.com

The AZOTE® Process Premium

- ◆ Thermo-formable
- ◆ Vacuum Formable
- ◆ Splittable
- ◆ High Quality Surface Finish
- ◆ Heat Stable
- ◆ Thermal Bonding
- ◆ Water Jet Cutting
- ◆ Robust Edges
- ◆ Ductile
- ◆ Reduced Resin Uptake
- ◆ Reduced Adhesive Uptake

Visit our website www.zotefoams.com



LinkedIn

AZOTE®, PLASTAZOTE®, EVAZOTE® and SUPAZOTE® are registered trademarks of Zotefoams plc.

0013/Insulation Azote/English/05/4/500
Copyright © 2016 Zotefoams plc